

View Online at <https://aerobasegroup.com/nsn/5355-00-616-7669>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.640 inches

Counterbore Depth:

0.320 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.484 inches

Overall Depth:

0.730 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.890 inches and 0.930 inches

Skirt Style:

Stepped

Attachment Method:

Setscrews

Overall Thickness:

Between 0.980 inches and 1.040 inches

End Application:

Sonar sets, an/bqs-14a/15, helicopter, mh-53e, sonar acoustic miscellaneous, helicopter, advance attack, ah-1w, support equipment, b-52 aircraft, landing system automatic carrier, dual channel, tactical air opns module (an/tyq (23), airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a), aircraft, c-2a (reprocured)

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

0.845 inches

Skirt Design:

Nondetachable

Color:

Black, lusterless

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0