

NSN 5355-00-619-3835 Knob - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5355-00-619-3835 **Inside Diameter:** Between 0.252 inches and 0.254 inches **Counterbore Diameter:** 0.640 inches **Counterbore Depth:** 0.320 inches **Setscrew Hole Quantity:** 2 **Distance From Hole Center To Knob/skirt Base:** 0.484 inches **Overall Depth:** 0.730 inches **Gripping Surface Condition:** Grip aid **Shaft Accommodation Style:** Counterbored **Outside Diameter:** Between 0.890 inches and 0.930 inches **Skirt Style:** Flared **Reference Marking:** Arrow **Attachment Method:** Setscrews **Overall Thickness:** Between 0.980 inches and 1.040 inches **Material Transparency:** Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

1.525 inches

Skirt Design:

Nondetachable

Style Designator:

Round

Thread Series Designator:

Unc screw hole

NSN 5355-00-619-3835

Knob - Page 2 of 2



| S | pec | ific | cati | on | Data: |
|---|-----|------|------|----|-------|
| | | | | | |

96906-ms91528 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0