

View Online at <https://aerobasegroup.com/nsn/5355-00-619-4668>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.640 inches

Counterbore Depth:

0.114 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.260 inches

Overall Depth:

0.520 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.890 inches and 0.930 inches

Attachment Method:

Setscrews

Overall Thickness:

Between 0.760 inches and 0.820 inches

End Application:

W/s: traffic jam, an/tlq-17a; radar, series an/sps-4 (v); communications terminal, satellite an/gsc-39(v)1; sonar dome rubber windows (sdrws); sonar signal processing sys, an/sqq-28(v); aircraft (ac-130h, mc-130h, ec-130e, hc-130); aircraft, c-2a (reprocured); support equipment, b-1 aircraft; airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a)

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Color:

Black, lusterless

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms91528 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530m0