

View Online at <https://aerobasegroup.com/nsn/5355-00-644-2275>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.640 inches

Counterbore Depth:

0.320 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.484 inches

Overall Depth:

0.730 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.890 inches and 0.930 inches

Length:

Between 0.890 inches and 0.930 inches

Skirt Style:

Stepped

Attachment Method:

Setscrews

Overall Thickness:

Between 1.325 inches and 1.425 inches

End Application:

Virginia class cgn (41), kidd class ddg, spruance class dd (963), oliver perry class ffg, los angeles class ssn (688), emory s. Land class as, wasp class lhd, forrestal class cv, aircraft, (ac-130h, mc-130h, ec-130e, hc-130)

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

0.845 inches

Skirt Design:

Nondetachable

Special Features:

Tactile form-focus, 0.610 in. Min dia, 0.650 in. Maximum dia, 0.320 in. Min thickness, 0.370 in. Maximum thickness

Color:

Black, lusterless

Style Designator:

Round with cross face

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0