

View Online at <https://aerobasegroup.com/nsn/5355-00-656-1299>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.188 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

0.568 inches

Fluted Foil Quantity:

3

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.690 inches and 0.730 inches

Skirt Style:

Stepped

Attachment Method:

Setscrews

Overall Thickness:

Between 1.025 inches and 1.125 inches

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

0.680 inches

Skirt Design:

Nondetachable

Special Features:

Knob color is federal standard 595, no. 37038, tactile form-tune, 0.610 in. Min dia. 0.650 in. Maximum dia, 0.320 in. Min thickness, 0.370 in. Maximum thickness

Color:

Black, lusterless

Style Designator:

Round with fluted foils

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0