

View Online at <https://aerobasegroup.com/nsn/5355-00-656-1307>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.188 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

0.568 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.690 inches and 0.730 inches

Length:

Between 0.690 inches and 0.730 inches

Skirt Style:

Stepped

Attachment Method:

Setscrews

Overall Thickness:

Between 1.025 inches and 1.125 inches

End Application:

Helicopter, super jolly h-53, helicopter, green giant h-3, helicopter, search and rescue, hh-60h, aircraft black hawk (mh-60k special operations aircraft), helicopter, ch-53a/d/e, helicopter, sea king h-3, helicopter, mh-53e, helicopter, hh-53h pave low, helicopter, carrier based asw, sh-60f

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thread Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

0.680 inches

Skirt Design:

Nondetachable

Special Features:

Tactile form-focus, 0.610 in. Min dia, 0.650 in. Maximum dia, 0.320 in. Min thickness, 0.370 in. Maximum thickness

Style Designator:

Round with cross face

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0