

View Online at <https://aerobasegroup.com/nsn/5355-00-656-1458>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.026 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.187 inches

Overall Depth:

0.405 inches

Width:

Between 0.690 inches and 0.730 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Length:

Between 1.020 inches and 1.070 inches

Attachment Method:

Setscrews

Overall Thickness:

Between 0.580 inches and 0.640 inches

End Application:

Sonar sets, an/bqs-14a/15, radar, series an/sps-4 (v), deep submergence systems programs (dssp), computer display set, an/uyq-21(v), los angeles class ssn (688), sturgeonclass ssn (637), target acquisition system, mk-23 (mods 1-8), aircraft, (ac-130h, mc-130h, ec-130e, h; missile, air-to-air, sparrow (aim-7)

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Pointer Design:

Nondetachable

Color:

Black, lusterless

Style Designator:

Pointer

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0