

View Online at <https://aerobasegroup.com/nsn/5355-00-667-5522>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Shank Length:

0.235 inches

Shank Diameter:

0.845 inches

Shank Style:

Straight

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.484 inches

Overall Depth:

0.730 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Round

Outside Diameter:

Between 0.890 inches and 0.930 inches

Skirt Style:

Ring

Attachment Method:

Setscrews

Overall Thickness:

Between 1.325 inches and 1.425 inches

End Application:

Kidd class ddg, los angeles class ssn (688), ticonderoga class cg (47), spruance class dd (963), forrestal class cv, arleigh burkeclass ddg, aircraft,

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

0.640 inches

Skirt Design:

Nondetachable

Special Features:

W/tactile form-dimmer

Material:

Stainless steel

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0