

View Online at <https://aerobasegroup.com/nsn/5355-00-667-5522>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Shank Length:**

0.235 inches

**Shank Diameter:**

0.845 inches

**Shank Style:**

Straight

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.484 inches

**Overall Depth:**

0.730 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Round

**Outside Diameter:**

Between 0.890 inches and 0.930 inches

**Skirt Style:**

Ring

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 1.325 inches and 1.425 inches

**End Application:**

Kidd class ddg, los angeles class ssn (688), ticonderoga class cg (47), spruance class dd (963), forrestal class cv, arleigh burkeclass ddg, aircraft,

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

0.640 inches

**Skirt Design:**

Nondetachable

**Special Features:**

W/tactile form-dimmer

**Material:**

Stainless steel

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0