

View Online at <https://aerobasegroup.com/nsn/5355-00-667-9826>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.640 inches

Counterbore Depth:

0.114 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.260 inches

Overall Depth:

0.520 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.890 inches and 0.930 inches

Attachment Method:

Setscrews

Overall Thickness:

Between 1.106 inches and 1.206 inches

End Application:

Forrestal class cv, precision landing radar an/fpn-62, sonar, an/bsy- (v), virginia class cgn (41), los angeles class ssn (688), teletype, model 28, spruance class dd (963), ticonderoga class cg (47) , communications terminal, an/ugc-74

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thread Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Special Features:

Tactile form 4-gain

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms91528 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0