

View Online at <https://aerobasegroup.com/nsn/5355-00-680-1357>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.188 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

0.568 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.690 inches and 0.730 inches

Skirt Style:

Flared

Reference Marking:

Arrow

Attachment Method:

Setscrews

Overall Thickness:

Between 0.752 inches and 0.812 inches

End Application:

Untermeasure set, an/slq-32, support equipment, b-1 aircraft, aircraft,

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

1.150 inches

Skirt Design:

Nondetachable

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0