

View Online at <https://aerobasegroup.com/nsn/5355-00-703-8347>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.026 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.187 inches

Overall Depth:

0.405 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.690 inches and 0.730 inches

Attachment Method:

Setscrews

Overall Thickness:

Between 0.856 inches and 0.956 inches

End Application:

An/srn-2 (v) navigation radio set, whidbey islandclass lsd, oliver perry class ffg, spruance class dd (963), kidd class ddg, communications systems, an/wrr-7, los angeles class ssn (688), virginia class cgn (41), ticonderoga class cg (47)

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thread Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Special Features:

Tactile form-dimmer, 0.610 in. Min dia, 0.650 in. Maximum dia, 0.320 in. Min thickness, 0.370 in maximum thickness

Style Designator:

Round with bar face

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530m0