

View Online at <https://aerobasegroup.com/nsn/5355-00-703-8347>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.485 inches

**Counterbore Depth:**

0.026 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.187 inches

**Overall Depth:**

0.405 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.690 inches and 0.730 inches

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.856 inches and 0.956 inches

**End Application:**

An/srn-2 (v) navigation radio set, whidbey islandclass lsd, oliver perry class ffg, spruance class dd (963), kidd class ddg, communications systems, an/wrr-7, los angeles class ssn (688), virginia class cgn (41), ticonderoga class cg (47)

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thread Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Special Features:**

Tactile form-dimmer, 0.610 in. Min dia, 0.650 in. Maximum dia, 0.320 in. Min thickness, 0.370 in maximum thickness

**Style Designator:**

Round with bar face

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0