

View Online at <https://aerobasegroup.com/nsn/5355-00-721-8642>

**Inside Diameter:**

Between 0.251 inches and 0.252 inches

**Counterbore Diameter:**

0.750 inches

**Counterbore Depth:**

Between 0.255 inches and 0.265 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

Between 0.370 inches and 0.380 inches

**Overall Depth:**

Between 0.620 inches and 0.630 inches

**Gripping Surface Condition:**

Smooth

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.968 inches and 0.973 inches

**Skirt Style:**

Flared

**Reference Marking:**

Arrow

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.737 inches and 0.747 inches

**Screw Drive Type:**

Cross recess type 1

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

1.812 inches

**Skirt Design:**

Nondetachable

**Special Features:**

3-0.190-32 nf-2b holes in periphery of knob 0.600-0.604 in. From base

**Material:**

Aluminum alloy

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0