

View Online at <https://aerobasegroup.com/nsn/5355-00-727-1487>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.640 inches

**Counterbore Depth:**

0.320 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.484 inches

**Overall Depth:**

0.730 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.890 inches and 0.930 inches

**Skirt Style:**

Flared

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.980 inches and 1.040 inches

**End Application:**

Forrestal class cv, spruance class dd (963), helicopter, carrier based asw, sh-60f, ticonderoga class cg (47), sonar sets, an/bqs-14a/15, virginia class cgn (41), helicopter, uscg search and rescue, hh-60j, missile systems, nato sea sparrow, sturgeon class ssn (637), helicopter, search and rescue, hh-60h

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

1.525 inches

**Skirt Design:**

Nondetachable

**Color:**

Black, lusterless

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0