

View Online at <https://aerobasegroup.com/nsn/5355-00-728-4549>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.640 inches

**Counterbore Depth:**

0.320 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.484 inches

**Overall Depth:**

0.730 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.890 inches and 0.930 inches

**Skirt Style:**

Flared

**Reference Marking:**

Arrow

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.980 inches and 1.040 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

1.525 inches

**Skirt Design:**

Nondetachable

**Color:**

Gray, federal standard 595, 36231

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Specification Data:**

96906-ms91528 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0