

View Online at <https://aerobasegroup.com/nsn/5355-00-762-1493>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.485 inches

**Counterbore Depth:**

0.188 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.369 inches

**Overall Depth:**

Between 0.665 inches and 0.715 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.690 inches and 0.730 inches

**Skirt Style:**

Flared

**Reference Marking:**

Arrow

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.665 inches and 0.715 inches

**End Application:**

W/s: kidd class ddg; oliver perry class ffg; tarawa class lha; wasp class lhd; spruance class dd (963); forrestal class cv; over the horizon back scanner (oth-b) program (an/fps-118); ticonderoga class cg (47); sturgeon class ssn (637)

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Skirt Outside Diameter:**

1.150 inches

**Skirt Design:**

Nondetachable

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0