

View Online at <https://aerobasegroup.com/nsn/5355-00-813-2078>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Counterbore Diameter:

0.300 inches

Counterbore Depth:

0.177 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.325 inches

Overall Depth:

0.560 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.490 inches and 0.530 inches

Skirt Style:

Stepped

Attachment Method:

Setscrews

Overall Thickness:

Between 0.625 inches and 0.685 inches

End Application:

W/s: helicopter, mh-53e; aircraft (ac-130h, mc-130h, ec-130e, hc-130); deep submergence systems programs (dssp); fire control system, mk 92 (fcs); communications systems, an/wrr-7; support equipment, b-1 aircraft; aircraft, c-2a (reprocured); helicopter, advance attack, ah-1w; radar set, an/pps-5b

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

0.460 inches

Skirt Design:

Nondetachable

Color:

Black, lusterless

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0