

View Online at <https://aerobasegroup.com/nsn/5355-00-851-4953>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.750 inches

**Counterbore Depth:**

0.250 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.427 inches

**Overall Depth:**

0.605 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 1.240 inches and 1.280 inches

**Skirt Style:**

Stepped

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 1.325 inches and 1.425 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

1.185 inches

**Skirt Design:**

Nondetachable

**Special Features:**

Tactile form-gain, 1.136 in. Min dia, 1.176 in. Maximum dia, 0.665 in. Min thickness, 0.715 in. Maximum thickness

**Color:**

Black, lusterless

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0