

View Online at <https://aerobasegroup.com/nsn/5355-00-851-4953>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.750 inches

Counterbore Depth:

0.250 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.427 inches

Overall Depth:

0.605 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 1.240 inches and 1.280 inches

Skirt Style:

Stepped

Attachment Method:

Setscrews

Overall Thickness:

Between 1.325 inches and 1.425 inches

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

1.185 inches

Skirt Design:

Nondetachable

Special Features:

Tactile form-gain, 1.136 in. Min dia, 1.176 in. Maximum dia, 0.665 in. Min thickness, 0.715 in. Maximum thickness

Color:

Black, lusterless

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0