

View Online at <https://aerobasegroup.com/nsn/5355-00-852-0341>

Inside Diameter:

Between 0.251 inches and 0.252 inches

Counterbore Diameter:

Between 0.599 inches and 0.619 inches

Counterbore Depth:

Between 0.084 inches and 0.104 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

Between 0.224 inches and 0.244 inches

Overall Depth:

Between 0.428 inches and 0.448 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.740 inches and 0.760 inches

Skirt Style:

Flared

Attachment Method:

Setscrews

Overall Thickness:

Between 0.552 inches and 0.572 inches

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.138 inches screw hole

Skirt Outside Diameter:

Between 0.802 inches and 0.822 inches

Skirt Design:

Nondetachable

Pointer Design:

Nondetachable

Color:

Black

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0