

View Online at <https://aerobasegroup.com/nsn/5355-00-882-1246>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.369 inches

**Overall Depth:**

0.568 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Flatted one side

**Outside Diameter:**

Between 0.690 inches and 0.730 inches

**Skirt Style:**

Flared

**Reference Marking:**

Arrow

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.222 inches and 0.227 inches

**Overall Thickness:**

Between 0.752 inches and 0.812 inches

**End Application:**

Helicopter, search and rescue, hh-60h, los angelesclass ssn (688), aircraft, stratolifter c-135, aircraft, viking s-3b, aircraft, hawkeye e-2c, submarine acoustic sonar systems, helicopter, carrier based asw, sh-60f, aircraft, thunderbolt ii, a-10, sonar, an/bsy- (v)

**Screw Drive Type:**

Hexagon socket

**Thread Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Skirt Outside Diameter:**

1.150 inches

**Skirt Design:**

Nondetachable

**Special Features:**

Shaft accommodation hole couterbored 0.485 in. Min dia, 0.188 in. Min depth

**Color:**

White

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0