

View Online at <https://aerobasegroup.com/nsn/5355-00-882-1246>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

0.568 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Outside Diameter:

Between 0.690 inches and 0.730 inches

Skirt Style:

Flared

Reference Marking:

Arrow

Attachment Method:

Setscrews

Inside Width:

Between 0.222 inches and 0.227 inches

Overall Thickness:

Between 0.752 inches and 0.812 inches

End Application:

Helicopter, search and rescue, hh-60h, los angelesclass ssn (688), aircraft, stratolifter c-135, aircraft, viking s-3b, aircraft, hawkeye e-2c, submarine acoustic sonar systems, helicopter, carrier based asw, sh-60f, aircraft, thunderbolt ii, a-10, sonar, an/bsy- (v)

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

1.150 inches

Skirt Design:

Nondetachable

Special Features:

Shaft accommodation hole couterbored 0.485 in. Min dia, 0.188 in. Min depth

Color:

White

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0