

View Online at <https://aerobasegroup.com/nsn/5355-00-883-4609>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Shank Length:**

0.094 inches

**Shank Diameter:**

0.562 inches

**Shank Style:**

Straight

**Setscrew Hole Quantity:**

1

**Distance From Hole Center To Knob/skirt Base:**

Between 0.234 inches and 0.266 inches

**Overall Depth:**

Between 0.452 inches and 0.484 inches

**Width:**

Between 0.609 inches and 0.641 inches

**Fluted Foil Quantity:**

12

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Flatted one side

**Outside Diameter:**

Between 0.609 inches and 0.641 inches

**Skirt Style:**

Flared

**Reference Marking:**

Single line

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.222 inches and 0.224 inches

**Overall Thickness:**

Between 0.703 inches and 0.735 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

Between 1.240 inches and 1.260 inches

**Skirt Design:**

Nondetachable

**Color:**

Black

**Style Designator:**

Fluted foils

**Thread Series Designator:**

Unc screw hole

**Specification Data:**

96906-ms25167 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0