

View Online at <https://aerobasegroup.com/nsn/5355-00-883-4609>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Shank Length:

0.094 inches

Shank Diameter:

0.562 inches

Shank Style:

Straight

Setscrew Hole Quantity:

1

Distance From Hole Center To Knob/skirt Base:

Between 0.234 inches and 0.266 inches

Overall Depth:

Between 0.452 inches and 0.484 inches

Width:

Between 0.609 inches and 0.641 inches

Fluted Foil Quantity:

12

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Outside Diameter:

Between 0.609 inches and 0.641 inches

Skirt Style:

Flared

Reference Marking:

Single line

Attachment Method:

Setscrews

Inside Width:

Between 0.222 inches and 0.224 inches

Overall Thickness:

Between 0.703 inches and 0.735 inches

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

Between 1.240 inches and 1.260 inches

Skirt Design:

Nondetachable

Color:

Black

Style Designator:

Fluted foils

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms25167 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530m0