## NSN 5355-00-899-9014



Knob - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5355-00-899-9014 **Inside Diameter:** Between 0.252 inches and 0.254 inches **Setscrew Hole Quantity:** 2 Distance From Hole Center To Knob/skirt Base: 0.484 inches **Overall Depth:** 0.730 inches Width: Between 0.890 inches and 0.930 inches **Gripping Surface Condition:** Grip aid **Shaft Accommodation Style:** Flatted one side Length: Between 1.325 inches and 1.375 inches **Skirt Style:** Stepped **Attachment Method:** Setscrews **Inside Width:** Between 0.222 inches and 0.227 inches **Overall Thickness:** Between 0.980 inches and 1.040 inches **Screw Drive Type:** Hexagon socket Thready Qty Per Inch (tpi): 32 screw hole Thread Size: 0.164 inches screw hole **Skirt Outside Diameter:** 1.345 inches **Skirt Design:** Nondetachable **Pointer Design:** Nondetachable **Special Features:** Shaft accommodation hole counterbored, 0.640 in. Min dia, 0.320 in. Min depth Color: Black **Style Designator:** 

Pointer

## NSN 5355-00-899-9014

Knob - Page 2 of 2



Thread	Series	Design	ator:
	0000	- 00.9.	

Unc screw hole

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A530m0