

View Online at <https://aerobasegroup.com/nsn/5355-00-901-0595>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.260 inches

Overall Depth:

0.520 inches

Width:

Between 0.890 inches and 0.930 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Length:

Between 1.325 inches and 1.375 inches

Attachment Method:

Setscrews

Inside Width:

Between 0.222 inches and 0.227 inches

Overall Thickness:

Between 1.105 inches and 1.205 inches

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Pointer Design:

Nondetachable

Special Features:

Tactile form-range, 0.792 in. Min dia, 0.832 in. Maximum dia, 0.413 in. Min thickness, 0.463 in. Maximum thickness, shaft accommodation hole counterbore 0.640 in. Min dia, 0.114 in. Min depth

Style Designator:

Pointed with arched bar

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530m0