## NSN 5355-00-901-0595

Knob - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5355-00-901-0595 **Inside Diameter:** Between 0.252 inches and 0.254 inches **Setscrew Hole Quantity:** 2 **Distance From Hole Center To Knob/skirt Base:** 0.260 inches **Overall Depth:** 0.520 inches Width: Between 0.890 inches and 0.930 inches **Gripping Surface Condition:** Grip aid **Shaft Accommodation Style:** Flatted one side Length: Between 1.325 inches and 1.375 inches **Attachment Method:** Setscrews **Inside Width:** Between 0.222 inches and 0.227 inches **Overall Thickness:** Between 1.105 inches and 1.205 inches **Screw Drive Type:** Hexagon socket Thready Qty Per Inch (tpi): 32 screw hole **Thread Size:** 0.164 inches screw hole **Pointer Design:** Nondetachable **Special Features:** Tactile form-range, 0.792 in. Min dia, 0.832 in. Maximum dia, 0.413 in. Min thickness, 0.463 in. Maximum thickness, shaft accommodation hole counterbore 0.640 in. Min dia, 0.114 in. Min depth **Style Designator:** Pointed with arched bar **Thread Series Designator:** Unc screw hole Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5355-00-901-0595

Knob - Page 2 of 2



Fiig:

A530m0