

View Online at <https://aerobasegroup.com/nsn/5355-00-931-5383>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

0.568 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Outside Diameter:

Between 0.690 inches and 0.730 inches

Skirt Style:

Stepped

Reference Marking:

Dot

Attachment Method:

Setscrews

Inside Width:

Between 0.222 inches and 0.227 inches

Overall Thickness:

Between 0.752 inches and 0.812 inches

End Application:

W/s: los angeles class ssn (688); sonar sets, an/bqs-14a/15; landing system automatic carrier, dual channel; forrestal class cv; nimitz class cvn; sturgeon class ssn (637); spruance class dd (963); wasp class lhd; tarawa class lha; submarine (ssn) fire control sys

Screw Drive Type:

Hexagon socket

Thread Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

0.680 inches

Skirt Design:

Nondetachable

Special Features:

Shaft accommodation hole counterbored 0.485 in. Min dia, 0.188 in. Min depth

Color:

Black

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0