

View Online at <https://aerobasegroup.com/nsn/5355-00-931-5383>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.369 inches

**Overall Depth:**

0.568 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Flatted one side

**Outside Diameter:**

Between 0.690 inches and 0.730 inches

**Skirt Style:**

Stepped

**Reference Marking:**

Dot

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.222 inches and 0.227 inches

**Overall Thickness:**

Between 0.752 inches and 0.812 inches

**End Application:**

W/s: los angeles class ssn (688); sonar sets, an/bqs-14a/15; landing system automatic carrier, dual channel; forrestal class cv; nimitz class cvn; sturgeon class ssn (637); spruance class dd (963); wasp class lhd; tarawa class lha; submarine (ssn) fire control sys

**Screw Drive Type:**

Hexagon socket

**Thread Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Skirt Outside Diameter:**

0.680 inches

**Skirt Design:**

Nondetachable

**Special Features:**

Shaft accommodation hole counterbored 0.485 in. Min dia, 0.188 in. Min depth

**Color:**

Black

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0