

View Online at <https://aerobasegroup.com/nsn/5355-00-953-7403>

**Inside Diameter:**

Between 0.127 inches and 0.129 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.158 inches

**Overall Depth:**

0.405 inches

**Width:**

Between 0.490 inches and 0.530 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Flatted one side

**Length:**

Between 0.730 inches and 0.780 inches

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.107 inches and 0.112 inches

**Overall Thickness:**

Between 0.480 inches and 0.540 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Pointer Design:**

Nondetachable

**Special Features:**

Shaft accommodation hole counterbored 0.420 in. Min dia, 0.026 in. Min depth

**Color:**

Gray, federal standard 595, 36231

**Style Designator:**

Pointer

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0