

View Online at <https://aerobasegroup.com/nsn/5355-00-989-4269>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.188 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

0.568 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.690 inches and 0.730 inches

Skirt Style:

Flared

Reference Marking:

Arrow

Attachment Method:

Setscrews

Overall Thickness:

Between 0.752 inches and 0.812 inches

End Application:

W/s: sonar sets, an/bqs-14a/15; communications systems an/wsc-3; deep submergence systems programs (dssp); sonar, an/bsy- (v); helicopter, mh-53e; sturgeon class ssn (637); an/bqh-5 sonar data collecting set; los angeles class ssn (688); helicopter, carrier based asw, sh-60f; aircraft (ac-130h, mc-130h, ec-130e, hc-130)

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

1.150 inches

Skirt Design:

Nondetachable

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0