

View Online at <https://aerobasegroup.com/nsn/5355-00-999-8460>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.026 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.187 inches

Overall Depth:

0.405 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.690 inches and 0.730 inches

Attachment Method:

Setscrews

Overall Thickness:

Between 0.856 inches and 0.956 inches

End Application:

Los angeles class ssn (688), sonar signal processing sys, an/sqq-2 (v), radar set lt air traffic control (17m jul83) (an/tps-63)communications systems, an/wrr-7, spruance class dd (963), forrestal class cv, computer display set, an/uyq-21(v), ticonderoga class cg (47) , nimitz class cvn

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Special Features:

Tactile form-dimmer, 0.610 in. Min dia, 0.650 in. Maximum dia, 0.320 in. Min thickness, 0.370 in. Maximum thickness

Style Designator:

Round with bar face

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0