

View Online at <https://aerobasegroup.com/nsn/5355-01-015-4362>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

Between 0.665 inches and 0.715 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Outside Diameter:

Between 0.690 inches and 0.730 inches

Skirt Style:

Flared

Reference Marking:

Arrow

Attachment Method:

Setscrews

Inside Width:

Between 0.222 inches and 0.227 inches

Overall Thickness:

Between 0.665 inches and 0.715 inches

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

1.150 inches

Skirt Design:

Nondetachable

Special Features:

Color is federal standard 595, featgthe shaft accommodation hole counterbore 0.485 in. Min dia, 0.188 in. Min depth, color of knob is federal standard 595, no. 37038, color of arrow is federal standard 595, no. 37875

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0