

View Online at <https://aerobasegroup.com/nsn/5355-01-016-7895>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.187 inches

Overall Depth:

0.405 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Outside Diameter:

Between 0.690 inches and 0.730 inches

Reference Marking:

Dot

Attachment Method:

Setscrews

Inside Width:

Between 0.222 inches and 0.227 inches

Overall Thickness:

Between 0.580 inches and 0.640 inches

End Application:

Countermeasure set, an/slq-32, nimitz class cvn, ticonderoga class cg (47), arleigh burke class ddg, wasp class lhd, iff aims mk xii

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Special Features:

Shaft accommodation hole counterbored, 0.485 in. Min dia, 0.266 in. Min depth

Color:

Black

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms91528 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0