

View Online at <https://aerobasegroup.com/nsn/5355-01-024-3411>

**Inside Diameter:**

Between 0.127 inches and 0.129 inches

**Counterbore Diameter:**

Between 0.507 inches and 0.513 inches

**Counterbore Depth:**

0.062 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

Between 0.147 inches and 0.157 inches

**Overall Depth:**

0.359 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.690 inches and 0.720 inches

**Skirt Style:**

Flared

**Reference Marking:**

Dot and line and slot

**Attachment Method:**

Setscrews

**Overall Thickness:**

0.370 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Skirt Outside Diameter:**

Between 0.950 inches and 1.050 inches

**Skirt Design:**

Detachable

**Color:**

Gray

**Style Designator:**

Round with bar face

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0