

View Online at <https://aerobasegroup.com/nsn/5355-01-032-8320>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Setscrew Hole Quantity:

1

Distance From Hole Center To Knob/skirt Base:

0.250 inches

Overall Depth:

Between 0.490 inches and 0.510 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Outside Diameter:

0.875 inches

Skirt Style:

Flared

Reference Marking:

Line

Attachment Method:

Setscrews

Inside Width:

Between 0.222 inches and 0.224 inches

Overall Thickness:

0.688 inches

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

Between 1.240 inches and 1.260 inches

Skirt Design:

Nondetachable

Pointer Design:

Nondetachable

Special Features:

Shaft accomodation counterbored 0.641 in. Min, 0.673 in. Maximum diameter, 0.100 in. Min, 0.132 in. Maximum depth

Color:

Black

Style Designator:

Round with single pointed bar face

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms25169 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0