

View Online at <https://aerobasegroup.com/nsn/5355-01-032-8320>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Setscrew Hole Quantity:**

1

**Distance From Hole Center To Knob/skirt Base:**

0.250 inches

**Overall Depth:**

Between 0.490 inches and 0.510 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Flatted one side

**Outside Diameter:**

0.875 inches

**Skirt Style:**

Flared

**Reference Marking:**

Line

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.222 inches and 0.224 inches

**Overall Thickness:**

0.688 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

Between 1.240 inches and 1.260 inches

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Special Features:**

Shaft accomodation counterbored 0.641 in. Min, 0.673 in. Maximum diameter, 0.100 in. Min, 0.132 in. Maximum depth

**Color:**

Black

**Style Designator:**

Round with single pointed bar face

**Thread Series Designator:**

Unc screw hole

**Specification Data:**

96906-ms25169 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0