

View Online at <https://aerobasegroup.com/nsn/5355-01-039-7599>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Counterbore Diameter:

Between 0.507 inches and 0.513 inches

Counterbore Depth:

0.125 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.330 inches

Overall Depth:

0.422 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.690 inches and 0.720 inches

Length:

Between 0.860 inches and 0.880 inches

Skirt Style:

Flared

Reference Marking:

Line and slot

Attachment Method:

Setscrews

Overall Thickness:

1.095 inches

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

Between 0.995 inches and 1.005 inches

Skirt Design:

Detachable

Color:

Black

Material:

Plastic

Style Designator:

Round with fin lever

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0