

View Online at <https://aerobasegroup.com/nsn/5355-01-040-2122>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Shank Length:**

0.093 inches

**Counterbore Diameter:**

Between 0.507 inches and 0.513 inches

**Counterbore Depth:**

0.125 inches

**Shank Diameter:**

Between 0.617 inches and 0.623 inches

**Shank Style:**

Straight

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

Between 0.250 inches and 0.260 inches

**Overall Depth:**

0.422 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.690 inches and 0.720 inches

**Length:**

Between 0.850 inches and 0.880 inches

**Skirt Style:**

Flared

**Reference Marking:**

Line and slot

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.995 inches and 1.005 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

Between 0.995 inches and 1.005 inches

**Skirt Design:**

Detachable

**Color:**

Black

**Style Designator:**

Round with fin lever

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0