

View Online at <https://aerobasegroup.com/nsn/5355-01-045-5613>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.340 inches

**Overall Depth:**

0.620 inches

**Width:**

0.440 inches

**Gripping Surface Condition:**

Smooth

**Shaft Accommodation Style:**

Flatted one side

**Length:**

1.120 inches

**Skirt Style:**

Flared

**Reference Marking:**

Line

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.222 inches and 0.224 inches

**Overall Thickness:**

0.750 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

0.810 inches

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Special Features:**

Upper shaft accommodation hole counterbore 0.380 in. Diameter 0.220 in. Depth, lower shaft accommodation hole counterbore 0.660 in. Diameter 0.120 in. Depth

**Color:**

Gray, federal standard 595, 36231

**Style Designator:**

Bar with single pointer

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0