NSN 5355-01-045-5613



Knob - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5355-01-045-5613 **Inside Diameter:** Between 0.252 inches and 0.254 inches **Setscrew Hole Quantity:** 2 Distance From Hole Center To Knob/skirt Base: 0.340 inches **Overall Depth:** 0.620 inches Width: 0.440 inches **Gripping Surface Condition:** Smooth **Shaft Accommodation Style:** Flatted one side Length: 1.120 inches **Skirt Style:** Flared **Reference Marking:** Line **Attachment Method:** Setscrews **Inside Width:** Between 0.222 inches and 0.224 inches **Overall Thickness:** 0.750 inches **Screw Drive Type:** Hexagon socket Thready Qty Per Inch (tpi): 32 screw hole **Thread Size:** 0.164 inches screw hole **Skirt Outside Diameter:** 0.810 inches **Skirt Design:** Nondetachable **Pointer Design:** Nondetachable **Special Features:** Upper shaft accommodation hole counterbore 0.380 in. Diameter 0.220 in. Depth, lower shaft accommodation hole counterbore 0.660 in. Diameter 0.120 in. Depth

Color:

Gray, federal standard 595, 36231

NSN 5355-01-045-5613

Knob - Page 2 of 2



Sty	عا	D	26	ia	n	a	ŧ٥	r	
JLY	ı	יש	ငၥ	щ		а	ιv	ш	

Bar with single pointer

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0