

View Online at <https://aerobasegroup.com/nsn/5355-01-049-4142>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.187 inches

Overall Depth:

0.405 inches

Width:

Between 0.690 inches and 0.730 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Length:

Between 1.020 inches and 1.070 inches

Reference Marking:

Line

Attachment Method:

Setscrews

Inside Width:

Between 0.107 inches and 0.112 inches

Overall Thickness:

Between 0.580 inches and 0.640 inches

End Application:

Support equipment, b-1 aircraft, helicopter, search and rescue, hh-60h, arleigh burke class ddg, ticonderoga class cg (47), forrestal class cv, nimitz class cvn, helicopter, carrier based asw, sh-60f, radarset, an/tpn-18, tarawa class lha

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Pointer Design:

Nondetachable

Special Features:

Shaft accommodation hole counterbored 0.485 in; min dia, 0.026 in. Min depth

Style Designator:

Pointer

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms91528 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0