

View Online at <https://aerobasegroup.com/nsn/5355-01-052-5161>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.325 inches

Overall Depth:

0.560 inches

Width:

Between 0.490 inches and 0.530 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Length:

Between 0.730 inches and 0.780 inches

Skirt Style:

Stepped

Reference Marking:

Line

Attachment Method:

Setscrews

Inside Width:

Between 0.107 inches and 0.112 inches

Overall Thickness:

Between 0.625 inches and 0.685 inches

End Application:

Spruance class dd (963), central office, telephoneauto, blue ridge class lcc-19, fleet satellite comm terminal, an/tsc-96a, nimitzclass cvn, tarawa class lha, communications platform, air defense (adp), ticonderoga class cg (47), tactical air opns module (an/tyq (23) , anv/tacterm set, taam a00097

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

0.690 inches

Skirt Design:

Nondetachable

Pointer Design:

Nondetachable

Special Features:

Shaft accommodation hole counterbore 0.300 in. Min dia, 0.177 in. Min depth

Color:

Black

Style Designator:

Pointer

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0