

View Online at <https://aerobasegroup.com/nsn/5355-01-052-5161>

**Inside Diameter:**

Between 0.127 inches and 0.129 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.325 inches

**Overall Depth:**

0.560 inches

**Width:**

Between 0.490 inches and 0.530 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Flatted one side

**Length:**

Between 0.730 inches and 0.780 inches

**Skirt Style:**

Stepped

**Reference Marking:**

Line

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.107 inches and 0.112 inches

**Overall Thickness:**

Between 0.625 inches and 0.685 inches

**End Application:**

Spruance class dd (963), central office, telephoneauto, blue ridge class lcc-19, fleet satellite comm terminal, an/tsc-96a, nimitzclass cvn, tarawa class lha, communications platform, air defense (adp), ticonderoga class cg (47), tactical air opns module (an/tyq (23) , anv/tacterm set, taam a00097

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Skirt Outside Diameter:**

0.690 inches

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Special Features:**

Shaft accommodation hole counterbore 0.300 in. Min dia, 0.177 in. Min depth

**Color:**

Black

**Style Designator:**

Pointer

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0