NSN 5355-01-052-5908

Knob - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5355-01-052-5908 **Inside Diameter:** Between 0.127 inches and 0.129 inches **Counterbore Diameter:** 0.485 inches **Counterbore Depth:** 0.188 inches **Setscrew Hole Quantity:** 2 **Distance From Hole Center To Knob/skirt Base:** 0.369 inches **Overall Depth:** 0.568 inches **Gripping Surface Condition:** Grip aid **Shaft Accommodation Style:** Counterbored **Outside Diameter:** Between 0.690 inches and 0.730 inches Skirt Style: Stepped **Attachment Method:** Setscrews **Overall Thickness:** Between 1.025 inches and 1.125 inches **Screw Drive Type:** Hexagon socket Thready Qty Per Inch (tpi): 40 screw hole Thread Size: 0.112 inches screw hole **Skirt Outside Diameter:** 0.680 inches **Skirt Design:** Nondetachable **Special Features:** Tactile form-dimmer, 0.610 in. Min dia, 0.650 in. Maximum diameter 0.320 in. Min thickness, 0.370 in. Maximum thickness **Style Designator:** Round with bar face **Thread Series Designator:**

N/a

Unc screw hole
Shelf Life:

NSN 5355-01-052-5908

Knob - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A530m0