

View Online at <https://aerobasegroup.com/nsn/5355-01-064-1613>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

0.568 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Flatted one side

Outside Diameter:

Between 0.690 inches and 0.730 inches

Skirt Style:

Flared

Attachment Method:

Setscrews

Inside Width:

Between 0.107 inches and 0.112 inches

Overall Thickness:

Between 0.752 inches and 0.812 inches

End Application:

Helicopter, electronic countermeasures, eh-60a, helicopter, lamps mark iii, sh-60b, helicopter, carrier based asw, sh-60f, helicopter, search and rescue, hh-60h, helicopter, black hawk uh-60a

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

1.150 inches

Skirt Design:

Nondetachable

Special Features:

Shaft accommodation hole counterbored, 0.485 in. Min dia, 0.188 in. Min depth

Color:

Gray, federal standard 595, 36231

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0