

View Online at <https://aerobasegroup.com/nsn/5355-01-077-9799>

**Inside Diameter:**

Between 0.127 inches and 0.129 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

Between 0.230 inches and 0.270 inches

**Overall Depth:**

0.400 inches

**Width:**

Between 0.480 inches and 0.520 inches

**Gripping Surface Condition:**

Smooth

**Shaft Accommodation Style:**

Flatted, two sides parallel

**Length:**

Between 0.860 inches and 0.900 inches

**Skirt Style:**

Flared

**Reference Marking:**

Line

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.107 inches and 0.109 inches

**Overall Thickness:**

Between 0.540 inches and 0.580 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Skirt Outside Diameter:**

Between 0.860 inches and 0.900 inches

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Special Features:**

Shaft accommodation hole counterbored, 0.245 in. Min dia, 0.265 in. Maximum dia, 0.080 in. Min depth, 0.120 in. Maximum depth

**Color:**

Black

**Style Designator:**

Bar with double pointer

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0