

View Online at <https://aerobasegroup.com/nsn/5355-01-077-9799>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

Between 0.230 inches and 0.270 inches

Overall Depth:

0.400 inches

Width:

Between 0.480 inches and 0.520 inches

Gripping Surface Condition:

Smooth

Shaft Accommodation Style:

Flatted, two sides parallel

Length:

Between 0.860 inches and 0.900 inches

Skirt Style:

Flared

Reference Marking:

Line

Attachment Method:

Setscrews

Inside Width:

Between 0.107 inches and 0.109 inches

Overall Thickness:

Between 0.540 inches and 0.580 inches

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

Between 0.860 inches and 0.900 inches

Skirt Design:

Nondetachable

Pointer Design:

Nondetachable

Special Features:

Shaft accommodation hole counterbored, 0.245 in. Min dia, 0.265 in. Maximum dia, 0.080 in. Min depth, 0.120 in. Maximum depth

Color:

Black

Style Designator:

Bar with double pointer

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0