

View Online at <https://aerobasegroup.com/nsn/5355-01-078-3497>

**Inside Diameter:**

Between 0.080 inches and 0.082 inches

**Counterbore Diameter:**

0.370 inches

**Counterbore Depth:**

Between 0.011 inches and 0.041 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.158 inches

**Overall Depth:**

0.406 inches

**Gripping Surface Condition:**

Smooth

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.530 inches and 0.570 inches

**Reference Marking:**

Dot

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.480 inches and 0.540 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Special Features:**

Slip clutch has 6 detents, with torque pounds per square inch of 1.0 min 1.5 max

**Color:**

Gray, federal standard 595, 36231

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0